

CARSTOPPER 30

AVAILABLE AS A STATIC BOLLARD OR REMOVABLE BOLLARD



PRODUCT OVERVIEW

CARSTOPPER 30 IS ONE OF THE SHALLOWEST IMPACT TESTED BOLLARDS AVAILABLE ON THE MARKET TODAY, WITH A FOUNDATION DEPTH OF JUST 200MM, REDUCING THE NEED TO RE-DIVERT UTILITIES. THIS ALLOWS FOR INSTALLATION AT A FRACTION OF THE COST OF TRADITIONAL BOLLARDS.

UNLIKE TRADITIONAL STEEL TUBE BOLLARDS, SAFETYFLEX'S CARSTOPPER 30 UTILISES OUR PATENTED SPRING STEEL DESIGN, CREATING A DURABLE, ULTRA SLIMLINE PRODUCT THAT IS IDEAL FOR BLENDING INTO THE PUBLIC REALM.

THE CARSTOPPER 30 SYSTEM IS DESIGNED TO FOLLOW THE CONTOURS OF THE GROUND SO CAN MANOEUVRE AROUND CORNERS, BENDS, AND CAN BE INSTALLED ON A INCLINE.

FINISHES

ROUND 316 STAINLESS STEEL MITRE TOP SHROUD WITH UP TO 2 HI-VIS BANDS AS STANDARD.

ALTERNATIVE FINISHES AVAILABLE. PLEASE CONTACT YOUR SALES REPRESENTATIVE FOR MORE DETAILS.

BANDING COLOUR OPTIONS

- > BLACK
- > YELLOW
- > RED
- > BLUE
- > ORANGE
- > WHITE
- > NO BANDING

APPLICATIONS

- > PUBLIC REALM
- > STADIA
- > RETAIL PARKS
- > LEISURE ATTRACTIONS
- > CRITICAL INFRASTRUCTURE
- > POLICE STATIONS
- > GOVERNMENT BUILDINGS

CARSTOPPER 30 SPECIFICATION DETAILS

SHROUD MEASUREMENTS	114MM Ø X 950MM H FROM FFL
BOLLARD SPACING	1290MM CENTRES, 1200MM SPACING BETWEEN TESTED CORES
HEIGHT ABOVE GROUND	850MM
SECURITY RATING	(BSI PAS68:2010) V/1500(M1)/48/90:1.8/0.0
TESTED CORE DIMENSIONS	90MM W X 73MM L X 850MM H FROM FFL
MINIMUM ARRAY	ONE
SHROUD MATERIAL	316 SATIN POLISHED STAINLESS STEEL AS STANDARD
RAL OPTIONS	ANY STANDARD RAL COLOUR
FOUNDATION DEPTH	200MM

REVISION

00/2023